



LIVE TO PLAY LIVE®

FUZZFACE®



JIMDUNLOP.COM

92503014462revB

FFM2 GERMANIUM MINI DISTORTION

FFM2 GERMANIUM FUZZ FACE® MINI DISTORTION

DESCRIPTION

- Legendary Fuzz Face tone with pedalboard-friendly size, AC power and on/bypass status LED
- Based on '66-'68 era pre-silicon Fuzz Face pedals
- Warm vintage fuzz tones provided by slightly mismatched germanium transistors
- True bypass

POWER

The FFM2 is powered by one 9-volt battery (open battery door on underside of pedal to install), a 9-volt AC adapter such as the Dunlop ECB003/ECB003EU, or a DC Brick™ power supply.

DIRECTIONS


- Run a cable from your guitar to the FFM2's INPUT jack and another cable from the FFM2's OUTPUT jack to your amplifier.
- Start with both controls at 12 o'clock.
- Turn the effect on by depressing the footswitch.
- Rotate the VOLUME knob clockwise to increase overall effect volume or counterclockwise to decrease it.
- Rotate the FUZZ knob clockwise to increase amount of fuzz or counterclockwise to decrease it.

SPECIFICATIONS

Input Impedance	10 kΩ
Output Impedance	
Max Volume	2 kΩ
-6 dB Volume	115 kΩ
Max Gain	45 dB
Bypass	True Hardwire
Current Draw	3.4 mA
Power Supply	9 volts DC

CONTROLS

- 1** VOLUME knob controls overall effect volume
- 2** FUZZ knob controls amount of fuzz
- 3** FOOTSWITCH toggles on/bypass (blue LED indicates on)



DUNLOP MANUFACTURING, INC.
P.O. BOX 846 BENICIA, CA 94510 U.S.A.
TEL: 1-707-745-2722 FAX: 1-707-745-2658